

Application No. 09/727,744
Amendment dated November 24, 2004
Reply to Office Action dated August 24, 2004

Amendments to the Claims

This listing of claims will replace all prior versions, and listings of claims in the application.

Listing of Claims

1 1. (Currently Amended) A method for processing a conditional jump
2 instruction storing a digital value to memory in a pipelined instruction processor, wherein
3 ~~the digital value is read from memory in response to a conditional jump instruction to~~
4 ~~determine if the condition of the conditional jump instruction is satisfied~~, the method
5 comprising:
6 generating at least one status bit based on ~~[[the]]~~ a digital value to be stored, the at
7 least one status bit relating to a particular condition of a conditional jump instruction and
8 specifying if the particular condition of the conditional jump instruction is satisfied or
9 not; ~~[[and]]~~
10 storing the digital value and the at least one status bit to a memory; and
11 in response to a conditional jump instruction, reading from the memory the digital
12 value and the at least one status bit to determine if the condition of the conditional jump
13 instruction is satisfied without having to submit the condition of the conditional jump
14 instruction to an arithmetic logic stage of the pipelines instruction processor.

1 2. (Cancel)

1 3. (Previously Presented) The method recited in claim 1, wherein the
2 at least one status bit is read from memory at the same time as the digital value.

Application No. 09/727,744
Amendment dated November 24, 2004
Reply to Office Action dated August 24, 2004

1 4. (Previously Presented) The method recited in claim 1, wherein the
2 memory has one or more addressable locations, and the at least one status bit is stored at
3 the same addressable location as the corresponding digital value.

1 5. (Previously Presented) The method recited in claim 1, wherein the
2 at least one status bit is set high if the digital value is zero.

1 6. (Previously Presented) The method recited in claim 1, wherein the
2 at least one status bit is set high if the digital value is a positive value.

1 7. (Previously Presented) The method recited in claim 1, wherein the
2 at least one status bit is set high if the digital value is negative.

1
1 8. (Previously Presented) The method recited in claim 1, wherein the
2 at least one status bit is set high if the digital value is a non zero value.

1
1 9. (Previously Presented) The method recited in claim 1, wherein the
2 at least one status bit is set high based on the value of the least significant bit of the
3 digital value.

Application No. 09/727,744
Amendment dated November 24, 2004
Reply to Office Action dated August 24, 2004

1 10. (Currently Amended) In a pipelined instruction processor that executes
2 instructions including conditional jump instructions, one or more of the conditional jump
3 instructions reading a digital value from memory to determine if the condition of the
4 conditional jump instruction is satisfied, the improvement comprising:
5 a status bit generator for generating at least one status bit based on a digital value,
6 the at least one status bit relating to a particular condition of a conditional jump
7 instruction and specifying if the particular condition of the conditional jump instruction
8 is satisfied or not; [[and]]
9 storing means for storing the digital value and the at least one status bit to the
10 memory; and
11 conditional jump processing means, activated in response to the execution of a
12 conditional jump instruction, the conditional jump processing means reading from the
13 memory the digital value and the at least one status bit to determine if the condition of the
14 conditional jump instruction is satisfied without having to submit the condition of the
15 conditional jump instruction to an arithmetic logic stage of the pipelines instruction
16 processor.

11. (Cancel)

1 12. (Previously Presented) The pipelined instruction processor recited
2 in claim 10, wherein the at least one status bit is read from the memory at the same time
3 as the digital value is read.

Application No. 09/727,744
Amendment dated November 24, 2004
Reply to Office Action dated August 24, 2004

1 13. (Previously Presented) The pipelined instruction processor recited
2 in claim 10, wherein the memory has one or more addressable locations, and the at least
3 one status bit is stored at the same addressable location as the corresponding digital
4 value.

1 14. (Previously Presented) The pipelined instruction processor recited
2 in claim 10, wherein the at least one status bit is set high if the digital value is zero.

1 15. (Previously Presented) The system recited in claim 10, wherein the
2 at least one status bit is set high if the digital value is a positive value.

1 16. (Previously Presented) The system recited in claim 10, wherein the
2 at least one status bit is set high if the digital value is negative.

1 17. (Previously Presented) The system recited in claim 10, wherein the
2 at least one status bit is set high if the digital value is a non zero value.

1 18. (Previously Presented) The system recited in claim 10, wherein the
2 at least one status bit is set high based on the value of the least significant bit of the
3 digital value.

Application No. 09/727,744
Amendment dated November 24, 2004
Reply to Office Action dated August 24, 2004

1 19. (Previously Presented) In a pipelined instruction processor that
2 executes instructions including conditional jump instructions, one or more of the
3 conditional jump instructions reading a digital value from memory to determine if the
4 condition of the conditional jump instruction is satisfied, the improvement comprising:
5 a plurality of addressable registers, each of the addressable registers storing a
6 value that includes a digital value and at least one jump status bit;
7 logic to access a current instruction, wherein the current instruction includes an
8 address and a corresponding jump field, the address identifies one of the addressable
9 registers and the corresponding jump field identifies a jump status bit of the at least one
10 jump status bits within the identified addressable register;
11 a jump look-ahead controller for generating a jump look-ahead signal using the
12 address that identifies one of the addressable registers and the jump field that identifies a
13 jump status bit within the identified addressable register, the jump look-ahead signal is a
14 function of the identified jump status bit;
15 tracking logic for tracking the addresses of a predetermined number of previous
16 instructions in the pipelined instruction processor and comparing the addresses of each
17 previous instruction to the address of the current instruction to generate a series of jump
18 disable signals; and

Application No. 09/727,744
Amendment dated November 24, 2004
Reply to Office Action dated August 24, 2004

19 conflict detection logic for generating a jump early signal using the jump look-
20 ahead signal and the series of jump disable signals, the jump early signal initiates the
21 conditional jump depending on the values of the jump disable signals.

1 20. (Previously Presented) The pipelined instruction processor as
2 recited in claim 19, wherein each jump status bit is dependent on the digital value stored
3 in the corresponding addressable register.

1

1 21. (Previously Presented) The pipelined instruction processor as
2 recited in claim 19, further comprising a bit status generator for generating the
3 corresponding jump status bits.

1 22. (Previously Presented) The pipelined instruction processor as
2 recited in claim 19, further comprising a prediction logic block responsive to the jump
3 early signal for implementing a prediction algorithm to predict the conditional jump
4 depending on the values of the jump disable signals.

1 23. (Previously Presented) The pipelined instruction processor as
2 recited in claim 19, wherein the tracking logic includes a queue for sequentially storing a
3 pre-determined number of instructions prior to sequentially piping the pre-determined
4 number of instructions through a read stage and decode stage in a pre-fetch pipeline.

Application No. 09/727,744
Amendment dated November 24, 2004
Reply to Office Action dated August 24, 2004

1 24. (Previously Presented) The pipelined instruction processor as
2 recited in claim 23, wherein the pre-determined number of instructions are sequentially
3 piped through an execution pipeline after being piped through a pre-fetch pipeline, the
4 execution pipeline includes a write-back stage.

1

1 25. (Previously Presented) The pipelined instruction processor as
2 recited in claim 24, wherein the addressable register is written during the write-back
3 stage.

1 26. (Previously Presented) The pipelined instruction processor as
2 recited in claim 25, wherein the execution pipeline further includes an address generation
3 stage, a present address stage, an output operand stage, a capture data stage, and an
4 arithmetic operation stage, all before the write-back stage.

1 27. (Currently Amended) A method for determine if a condition of a
2 conditional jump instruction is satisfied in a pipelined instruction processor, the
3 method comprising:
4 storing a digital value and one or more jump status bits that are based on the
5 digital value in [[each]] one or more of a plurality of address locations in an
6 addressable memory;

Application No. 09/727,744
Amendment dated November 24, 2004
Reply to Office Action dated August 24, 2004

7 accessing a current instruction, the current instruction having an address and a
8 jump field, the address identifies a selected address location of the addressable
9 memory, and the jump field identifies a selected jump status bit of the selected
10 address location;

11 generating a jump look-ahead signal that is a function of the selected jump
12 status bit read from the selected address location of the addressable memory, the
13 identified jump status bit is accessed using the address and the jump field of the
14 current instruction;

15 tracking the addresses of a predetermined number of previous instructions in
16 the pipelined instruction processor and comparing the addresses to the address of the
17 current instruction to generate a series of jump disable signals; and

18 generating a jump early signal using the jump-look ahead signal and the series
19 jump disable signals, the jump early signal initiates a conditional jump depending on
20 the value of the jump disable signals.